



4K AUTOCLAVABLE CAMERA HEAD/4K CAMERA HEAD

CH-S400-XZ-EA/EB

Clear Image in Every Condition



Sharper Images with Less Noise with the 4K Exmor R® **CMOS Sensor and Optical-Fiber Transmission**

- · High sensitivity
- · Less noise (dual noise-reduction function)
- · No delay (4K high-speed transmission)

Optimal View (Fast and Accurate)

- · One-Touch Auto Focus function always enables surgeons to see the fine details of tissue/texture
- · Electronic zoom allows surgeons to observe the fine patterns and structures of tissues in the body - in high precision even when enlarged

Improved Operability (Ergonomic Design)

- · Small, compact camera head
- · New coupler design

V-Pro Compatibility

Autoclave Compatibility (CH-S400-XZ-EA only)

· Reduced costs compared with other sterilization methods

Innovation by Sony & Olympus







		CH-400-XZ-EA	CH-400-XZ-EB
Order Number		N5404730	N5401730
Size	Camera head dimensions (unit: mm)	43.6 39.7	122.5
	Camera head weight	280 g	
	Cable	ø 5.1 mm × 3 m	
Observation	Pickup system	CMOS image sensor	
	Focal length	f = 23.5 mm	
NBI observation mode		Available	
Records of camera head nformation		Available	
Electronic shutter function		Available	
Electronic zoom function		Available	
Cleaning/ Disinfection/	Cleaning/disinfection	Immersible in disinfectant solution	
Sterilization	Sterilization	Autoclavable/V-Pro/ETO/Sterrad	V-Pro/ETO/Sterrad
Classification (electro-	Degree of protection against electric shock	TYPE BF	
medical equipment)	Degree of protection against explosion	The camera head should be kept away from flammable gases	

* For more details, refer to the instruction manual for the OTV-S400.

As medical knowledge is constantly growing, technical modifications or changes of the product design, product specifications, accessories and service offerings may be required.



Phone: +49 40 23773-0, Fax: +49 40 233765

www.olympus-europa.com