

1524 Micro Centrifuge



Features

- 24 x 2.0 mL dedicated air ventilated microcentrifuge, 15,000 RPM / 21,206 xg.
- Quick Acc / Dec time of ≤15 sec.
- Compact and light-weight design.
- ‘Snap-fit’ rotor for quick and easy task setup.
- Simultaneous display of all parameters.
- Numeric input keypad and Icon buttons.

Technical Specifications

Max. RPM/RCF for Fixed Angle	15,000 rpm / 21,206 xg
Max. Capacity for Fixed Angle	24 x 1.5/2.0 mL
Acc. Time to Max. Speed	≤15 sec
Dec. Time from Max. Speed	≤15 sec
Time Control	Pulse, timed <100 min or continuous
Time Counting Range	Selectable, at set speed or from starting
RCF/RPM Conversion	Yes
Noise Level (dependent on rotor)	≤60 dB

ACC/DEC Ramps	9/10
Program Memory	100
Power Supply	AC 230V, 50Hz (AC 220-230V, 60/50Hz; 110V optional)
Power Requirement	450 VA
Dimension (W x D x H)	240 x 378 x 240 mm
Net Weight	11.9 kg
CE MARK	Yes
Cat No.	GZ-1524

Fixed Angle Rotor, GRF-m2.0-24

- **Capacity : 24 x 1.5 / 2.0 mL**
- Max. RPM : 15,000
- Max. RCF : 21,206 xg



Tube type (mL)	Max. RCF (xg)	Adaptor Cat. No.
0.5	10,290	GAS-m0.5(2)
0.2	8,863	GAS-m0.2(2)